



JOHN DEERE

ENGINE PERFORMANCE CURVE

Rating: Gross Power


Application: Industrial
Intermittent / Continuous

POWERTECH 2.9L Engine

Model: 3029TV100
[Option 16QX]

70 hp @ 2500 rpm

52 kW @ 2500 rpm



Air Intake Restriction 12 in.H₂O (3 kPa)
Exhaust Back Pressure 30 in.H₂O (7.5 kPa)

Gross power guaranteed within + or - 5% at SAE J1995 and ISO 3046 conditions:

77 °F (25 °C) air inlet temperature
29.31 in.Hg (99 kPa) barometer
104 °F (40 °C) fuel inlet temperature
0.853 fuel specific gravity @ 60 °F (15.5 °C)

Conversion factors:

Power: kW = hp x 0.746

Fuel: 1 gal = 7.1 lb, 1 L = 0.85 kg

Torque: N·m = lb-ft x 1.356

All values are from currently available data and are subject to change without notice.

Notes:

Tier-1 Emission Certifications:

Certified by:

Ref: CARB; EPA; EU*
Engine Emission Label

* Revised Data

Curve: 3029TV100 Sheet 1 of 2

Nov 2021

Common Specifications:

General Data

Models (with auxiliary drive).....	5202 SAE A
(without auxiliary drive).....	5299
Number of Cylinders	3
Bore and Stroke--in. (mm).....	4.19 x 4.33 (106 x 110)
Displacement--in. ³ (L)	179 (2.9)
Compression Ratio	17.2:1*
Valves per Cylinder--Intake/Exhaust	1/1
Firing Order	1-2-3
Combustion System	Direct Injection
Engine Type	In-line, 4-Cycle
Aspiration	Turbocharged
Engine Crankcase Vent System.....	Open
Maximum Crankcase Pressure--in. H ₂ O (kPa)	2 (0.5)

Physical Data

Without A/D With A/D

Length--in. (mm)	28.2 (716) ...28.2 (716)
Width--in. (mm)	20.4 (519) ...20.8 (528)
Height--in. (mm)	36.5 (928) ...36.5 (928)
Weight, dry--lb (kg)	722 (328) ...724 (329)
(Includes SAE 4 flywheel housing, RE28119 flywheel, starter and electrics.)	
Center of Gravity Location	
From Rear Face of Block (X-axis)--in. (mm)	7.9 (201)
Right of Crankshaft (Y-axis)--in. (mm)	0.1 (-3)
Above Crankshaft (Z-axis)--in. (mm)	6.1 (155)
Max. Allow. Static Bending Moment at Rear	
Face of Flywhl Hsg w/ 5-G Load--lb-ft (N•m) ...	600 (814)
Thrust Brng. Load Limit (Forward)--lb (N) [I].....	900 (4003)
[C]	500 (2224)

Fuel System

Fuel Injection Pump	Stanadyne
Governor Regulation	7-10 %
Governor Type.....	Mechanical
Total Fuel Flow--lb/hr (kg/hr)	217 (98)
Fuel Consumption--lb/hr (kg/hr) [I].....	27.1 (12.3)
[C]	24.4 (11.1)
Maximum Fuel Transfer Pump Suction--ft (m) fuel....	3 (0.9)
Fuel Filter Micron Size @ 98% Efficiency	8

Engine Specification Data

Lubrication System

Oil Pressure at Rated Speed--psi (kPa).....	50 (345)
Oil Pressure at Low Idle--psi (kPa)	15 (105)
In Pan Oil Temperature--°F (°C)	240 (115)
Oil Pan Capacity, High--qt (L)	8 (7.6)
Oil Pan Capacity, Low--qt (L)	7 (6.6)
Total Engine Oil Capacity with Filters--qt (L).....	9 (8.5)
Engine Angularity Limits, Any Direction--Degrees [I]	30
[C]	20

Air System

Maximum Allowable Temp Rise--Ambient Air to	
Engine Inlet--°F (°C)	15 (8)
Maximum Air Intake Restriction	
Dirty Air Cleaner--in. H ₂ O (kPa)	25 (6.25)
Clean Air Cleaner--in. H ₂ O (kPa).....	12 (3)
Engine Air Flow--ft ³ /min (m ³ /min) [I]	178 (5)
[C]	151 (4.3)
Intake Manifold Pressure--psi (kPa) [I].....	13 (90)
[C]	11 (75)
Recommended Intake Pipe Diameter--in. (mm) ..	2.5 (63.5)

Cooling System

Engine Heat Rejection--BTU/min (kW) [I]	1820 (32)
[C]	1650 (29)
Coolant Flow--gal/min (L/min).....	38.5 (145)
Thermostat Start to Open--°F (°C)	180 (82)
Thermostat Fully Open--°F (°C).....	202 (94)
Max. Water Pump Inlet Restriction--in. H ₂ O (kPa)....	40 (10)
Engine Coolant Capacity--qt (L)	6 (5.7)
Recommended Pressure Cap--psi (kPa)	10 (69)
Maximum Top Tank Temp--°F (°C).....	221 (105)
Minimum Coolant Fill Rate--gal/min (L/min)	3 (11)
Min. Limiting Ambient Temperature--°F (°C).....	108 (42)

Exhaust System

Exhaust Flow--ft ³ /min (m ³ /min) [I].....	409 (166)
[C]	370 (105)
Exhaust Temperature--°F (°C) [I].....	844 (451)
[C]	806 (430)
Max. Allowable Back Pressure--in. H ₂ O (kPa).....	30 (7.5)
Rec'd. Exhaust Pipe Diameter--in. (mm)	2.5 (63.5)

Electrical System

Recommended Battery Capacity (CCA)	
12 Volt System--amp	640
24 Volt System--amp	570
Maximum Allowable Starting Circuit Resistance	
12 Volt System--Ohm	0.0012
24 Volt System--Ohm.....	0.002
Starter Rolling Current--12 Volt System	
At 32 °F (0 °C)--amp.....	780
At -22 °F (-30 °C)--amp.....	1000
Starter Rolling Current--24 Volt System	
At 32 °F (0 °C)--amp.....	600
At -22 °F (-30 °C)--amp	700

Performance Data

Rated Power--hp (kW) [I].....	70 (52)
[C]	63 (47)
Rated Speed--rpm	2500
Peak Torque--lb-ft (N•m) [I].....	176 (239)
[C]	158 (215)
Peak Torque Speed--rpm.....	1600
Low Idle Speed--rpm	850
BMEP--psi (kPa) [I].....	124 (855)
[C]	111 (765)
Friction Power @ Rated Speed--hp (kW).....	26 (19)
Altitude Capability -- ft (m)	10,500 (3200)*
Ratio--Air : Fuel [I]	32:1
[C]	33:1
Smoke @ Rated Speed--Bosch No [I].....	1.5
[C]	1.2
Noise--dB(A) @ 1 m	
No Aux Drive Aux Drive	
[I]	NA
[C]	NA

Engine Speed rpm	Contin. Limit hp(kW)	Intermit. Power hp(kW)	Intermit. Torque lb-ft(N•m)	BSFC lb/hp-hr (g/kWh)
2500	63 (47)	70 (52)	147 (199)	0.388 (236)
2400	63 (47)	70 (52)	153 (207)	0.378 (230)
2200	63 (47)	70 (52)	166 (226)	0.365 (222)
2000	59 (44)	66 (49)	173 (234)	0.360 (219)
1800	53 (40)	59 (44)	172 (233)	0.363 (221)
1600	48 (36)	54 (40)	176 (239)	0.370 (225)
1400	---	46 (34)	171 (232)	0.378 (230)
1200	---	36 (27)	158 (215)	0.383 (233)
1000	---	28 (21)	148 (201)	0.390 (237)

All values at rated speed and power with standard options unless otherwise noted.

[I] = Intermittent Data [C] = Continuous Data
Unless noted, all other values pertain to both.

* Revised Data
Curve: 3029TV100 Sheet 2 of 2

Nov 2021